

MAIN FEATURES



- Industrial twin water softener for reducing water hardness.
- Alternating running of the two bottles.
- Bottle manufactured in fiberglass reinforced polyester.
- Polyethylene brine tank with top cover.
- Automatic KERAMIS Valve 1" Top-mounting.
- Volumetric programmer with electronic operation and multicolor display.
- Down Flow Regeneration (DF).

TECHNICAL DATA

CONNECTION IN/OUT:	1"
CONTROL VALVE:	KERAMIS K73 1"
WATER METER:	YES (electronic)
POWER SUPPLY:	230 - 110 V / 50 - 60 Hz
RESIN VOLUME:	2 x 100 liters
SERVICE TEMPERATURE:	5 – 45 °C
SERVICE PRESSURE:	2 - 6 bar
MAX. FLOW:	3,5 m ³ / h
TREATED WATER BETWEEN REGENERATIONS: (Approximate values)	18,3 m ³ (30 °F) 13,8 m ³ (40 °F) 11,0 m ³ (50 °F)

RESIN TANK (2 units)

Volume:	105L (13 x 54 Top 2,5 ")
Material:	Bottle manufactured in fiberglass reinforced polyester.
Water Collectors:	Strainers 1"
336	336 mm x 1.380 mm

BRINE TANK (1 unit)

VOLUME:	300 L
MATERIAL:	High density polyethylene anti-UV
Dimensions (∅ x height):	680 mm x 1.140 mm